

(ग) Electrical Works

सि.नं		निर्माण सामाग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT) बाहेक			कैफियत
	सब सि.नं			आ.व ०७०/०७१	आ.व ०७१/०७२	आ.व ०७२/०७३	
1		Dyana White Plate series SWITCH SOCKET ANCHOR / CPL /NG/Flux OR ISI EQUIVALENT					
	1	One Gang one way switch	सेट	50	50	57	
	2	One Gang two way switch	सेट	58	58	67	
	3	One way bell switch	सेट	60	60	70	
	4	Two gang one way switch	"	86	86	94	
	5	Two gang one way switch with one bell push	"	90	90	102	
	6	Two gang Full two way switch	"	90	90	104	
	7	Three Gang one way switch	"	110	110	124	
	8	Four gang one way switch	"	134	134	156	
	9	Six gang one way switch (3x5)	"	221	221	246	
	10	Eight gang one way switch	"	264	264	295	
	11	Dimmer single 300 watt	"	252	252	300	
	12	Dimmer single 750 watt	"	377	377	445	
	13	5 Step humming free dimmer	"	514	514	395	
	14	16Amp 3 Pin Plug Top	"	76	76	117	
	15	1 switch with dimmer	"	354	354	357	
	16	6/16 Amp , 2/3 Pin Power sockets with switch & indicator	"	108	108	146	
	17	6/16 Amp , Power sockets with switch , indicator & safety shutter	"	108	108	164	
	18	20/25 A Single phase A.C. motor Starter with 6/16 Amp safty shutter power socket	"	360	360	360	
	19	32A D.P. switch with fuse & indicator Surface Mounting	"	137	137	200	
	20	6 Gang (86 mm x 220 mm) switch 2/3 pin switch socket shuttered socket & 2 nos. Humming free 5 steps fan dimmer with indicator	सेट	872	872	593	
	21	Blanking plate single	"	36	36	38	
	22	Telephone socket single	"	101	101	114	
	23	Telephone socket Double	"	142	142	164	
	24	Angle / bottom holder	"	34	34	34	
	25	Ceiling Rose	"	34	34	34	
	26	Buzzer	"	94	94	94	
	27	Musical bell	"	216	216	216	
	28	T.V.antena single Socket	"	68	68	80	
	29	6A 2/3 Pin unshuttered multi switch socket	"	110	110	124	
	30	RJ 45 Computer Socket for modem	"	152	152	228	
	31	Flush Mounting metallic Box for Plate Series switch / socket(78mm x 78mm x 50mm)	"	34	34	34	
	32	Flush Mounting metallic Box for Plate Series switch / socket 78 x 140 x 50	"	61	61	61	
	33	Flush Mounting metallic Box for Plate Series switch / socket 78 x205 x 50	"	95	95	95	
	34	Switch / socket outlet, Plate series having round switch buttons & white surrounding plate, suitable to fix on box size 3"x3" . ORANGE. or Equivalent					

सि.नं	सब सि.नं	निर्माण सामाग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT) बाहेक			कैफियत
				आ.व ०७०/०७१	आ.व ०७१/०७२	आ.व ०७२/०७३	
1.	1	10A 1gang 1way Switch	Set	81	81	81	
	2	10A 2gang 1way Switch	Set	158	158	158	
	3	10A 3gang 1way Switch	"	210	210	210	
	4	10A 4gang 1way Switch	"	340	340	340	
	5	10A 5gang 1way Switch	"	360	360	360	
	6	10A 6gang 1way Switch	"	599	599	599	
	7	10A 1gang 2way Switch	"	140	140	140	
	8	10A 2gang 2way Switch	"	270	270	270	
	9	10A 3gang 2way Switch	"	395	395	395	
	10	10A 4gang 2way Switch	"	595	595	595	
	11	T V Socket outlet	"	290	290	290	
	12	Telephone Socket	"	260	260	260	
	13	13A Universal socket outlet	"	450	450	450	
	14	13A Socket	"	265	265	265	
	15	15A switched Socket outlet	"	430	430	430	
	16	5A Socket	"	330	330	330	
		17	RJ 45 8way Computer Socket	"	800	800	800
	18	TV and Telephone Socket	"	575	575	575	
	19	7+2 PIN SOCKET OUTLET	"	900	900	900	
	20	3+2 PIN SOCKET OUTLET	"	560	560	560	
	21	X5 2+2 - 2 PIN SOCKET OUTLET	"	760	760	760	
	22	SCHUKO SOCKET WITH ONE SWITCH	"	490	490	490	
	23	Bell Press	"	230	230	230	
	24	Blank Plate	"	90	90	90	
	25	400W Light Dimmer W/ Switch	"	880	880	880	
	26	400W Fan Controller / Multi Step Dimmer	"	890	890	890	
	27	5 Step Fan Controller	"	870	870	870	
	28	2 Pin Socket W/ Switch	"	440	440	440	
	29	13A Twin Socket	"	660	660	660	
1		White Plate series modular type(polycarbonate) SWITCH SOCKET power pack,Bentex,Premier,Rathi,Ohms or EQUIVALENT					
	1	One Gang one way switch	सेट	50	50	97	
	2	One Gang two way switch	सेट	58	58	109	
	3	One way bell switch	सेट	60	60	109	
	4	Two gang one way switch	"	86	86	130	
	5	Two gang one way switch with one bell push	"	90	90	142	
	6	Two gang Full two way switch	"	90	90	154	
	7	Three Gang one way switch	"	110	110	162	
	8	Four gang one way switch	"	134	134	196	
	9	Six gang one way switch	"	221	221	298	
	10	Eight gang one way switch	"	264	264	363	
	11	Dimmer single 300 watt	"	252	252	472	
	15	1 switch with dimmer	"	354	354	485	
	16	6/16 Amp , 2/3 Pin Power sockets with switch & indicator	"	108	108	252	

सि.नं	सब सि.नं	निर्माण सामाग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT) बाहेक			कैफियत
				आ.व ०७०/०७१	आ.व ०७१/०७२	आ.व ०७२/०७३	
	17	6/13 Amp , Power sockets with switch , indicator	"	108	108	255	
	18	20 A D.P. switch with fuse & indicator Surface Mounting	"	137	137	344	
	19	4 Gang (86 mm x 220 mm) switch 2/3 pin switch socket with indicator	सेट	872	872	380	
	20	6 Gang (86 mm x 220 mm) switch 2/3 pin switch socket with indicator	सेट	872	872	460	
	21	Blanking plate single	"	36	36	60	
	22	Telephone socket single	"	101	101	147	
	23	Telephone socket Double	"	142	142	242	
	24	T.V. antenna single Socket	"	68	68	138	
	25	RJ 45 Computer Socket for modem	"	152	152	200	
	26	CAT-6 Computer Socket for modem	"	312	312	200	
2		Modular Type Switch Socket set NORTH-WEST' NORYSIS' ABB 'SCHNIEDER Legrand or ISI Equivalent					
	1	1P – 6A/10A 1 way switch	No.	140	140	135	
	2	1P – 16A/20A 1 way switch	"	230	230	216	
	3	1P – 25A 1 way switch	"	336	336	316	
	4	1P – 6A/10A 2 way switch	"	162	162	162	
	5	1P – 16A/20A 2 way switch	"	336	336	245	
	6	1P – 6A push button	"	176	176	179	
	7	1 gang blanking module	"	40	40	42	
	8	2 gang blanking module	"	80	80	83	
	9	FAN REGULATOR / DIMMER					
	10	Step type fan regulator	No.	672	672	620	
	11	60 – 500 W dimmer	"	880	880	774	
	12	1000 W dimmer	"	1,120	1,120	1629	
		SOCKETS / TELEPHONE / COMPUTER SOCKETS / TV SOCKETS					
	13	6A – multi socket 5 pin	No.	176	176	233	
	14	6/16A twin socket 3 pin (flushed)	"	240	240	322	
	15	6/16A twin socket 3 pin (projected)	"	240	240	322	
	16	25A 3 pin socket	"	336	336	389	
	17	13A 3 pin socket	"	260	260	262	
	18	RJ 11 telephone jack	"	128	128	154	
	19	RJ 45 cat.6e computer socket	"	640	640	541	
	20	TV socket	"	128	128	156	
		HOSPITALITY RANGE					
	21	250V/110V shaver socket	No.	992	992	4228	
	22	Indicator (DO NOT DISTUURB)	"	168	168	175	
	23	LED yellow night lamp	"	544	544	544	
	24	LED Blue night lamp	"	544	544	544	
		FRONT PLATE (COMPATIBLE TO MARKET BOXES) (White)		--	--		
	25	1 module front plate	No.	56	56	70	
	26	2 module front plate	"	56	56	74	
	27	3 module front plate	"	72	72	81	
	28	4 module front plate	"	80	80	87	
	29	6 module front plate	"	104	104	157	
	30	8 module front plate(4+4)	"	112	112	211	

सि.नं	सब सि.नं	निर्माण सामाग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT) बाहेक			कैफियत
				आ.व ०७०/०७१	आ.व ०७१/०७२	आ.व ०७२/०७३	
	31	8 module front plate (Horizontal)	"	112	112	169	
	32	12 module front plate	"	144	144	253	
	33	18 module front plate	"			339	
	2.2	Modular Type Switch Socket KOLORS/INDO ASIAN/ GOLD MEDAL/ANCHOR WOODS/ANCHOR ROMA/VIMAL WAVE or ISI Equivalent					
		Seperate Module for Modular Switch & Socket					
	1	1P – 6A/10A 1 way switch	No.	-	-	84	
	3	1P – 16A/20A 1 way switch	"	-	-	140	
	7	1P – 6A/10A 2 way switch	"	-	-	130	
	8	1P – 16A/20A 2 way switch	"	-	-	170	
	9	1P – 6A push button	"	-	-	130	
	11	1 gang blanking module	"	-	-	40	
	12	2 gang blanking module	"	-	-	76	
		FAN REGULATOR / DIMMER					
	13	Step type fan regulator	No.	-	-	680	
	14	60 – 500 W dimmer	"	-	-	580	
		SOCKETS / TELEPHONE / COMPUTER SOCKETS / TV SOCKETS					
	16	6A – multi socket 5 pin	No.	-	-	180	
	17	6/16A twin socket 3 pin (flushed)	"	-	-	280	
	18	6/16A twin socket 3 pin (projected)	"	-	-	280	
	20	13A 3 pin socket	"	-	-	180	
	21	RJ 11 telephone jack	"	-	-	140	
	22	RJ 45 cat.6e computer socket	"	-	-	230	
	23	TV socket	"	-	-	140	
	40	1 module front plate	No.	56	56	110	
	41	2 module front plate	"	56	56	110	
	42	3 module front plate	"	72	72	144	
	43	4 module front plate	"	80	80	160	
	44	6 module front plate	"	104	104	220	
	45	8 module front plate(4+4)	"	112	112	296	
	46	8 module front plate (Horizontal)	"	112	112	304	
	47	12 module front plate	"	144	144	352	
		18 module front plate	"			440	
		Flush mounting galvanized Metal box for modular type switch & socket					
	1	1 module metal box having L x B x Depth =(78x78x45)mm	सेट	50	50	50	
	2	2 module " " = (78x78x45)mm	"	50	50	50	
	3	3 gang " " " =(78x100x45)mm	"	54	54	54	
	4	4 gang " " =(78x140x50)mm	"	66	66	66	
	5	5 gang " " =(78x205x50)mm	"	130	130	130	
	6	6 gang " " =(78x205x50)mm	"	132	132	132	
	7	8 module metal box (4+4) =(78x230x60)mm	"	176	176	176	
	8	8 module metal box (Horizontal) =(135x120x60)mm	"	176	176	176	

सि.नं	सब सि.नं	निर्माण सामग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT) बाहेक			कैफियत
				आ.व ०७०/०७१	आ.व ०७१/०७२	आ.व ०७२/०७३	
	9	12 module metal box =(135x120x60)mm	"	224	224	224	
	10	TV socket metal box	"	50	50	50	
	11	Telephone socket metal box	"	50	50	50	
		METAL Junction BOX					
	1	4"x4"	गोटा	97	97	97	
	2	4"x6"	"	145	145	145	
	3	6"x8"	"	230	230	230	
	4	8"x10"	"	339	339	339	
	5	8"x12"	"	339	339	339	
		PVC Junction Box	"	33	33	33	
	1	4"x4"	गोटा				
	2	4"x6"	"	30	30	30	
	3	6"x8"	"	45	45	45	
	4	8"x10"	"	65	65	65	
	5	8" x12"	"	125	125	125	
		Junction box cover	"	140	140	140	
	5	PVC Listy Double Lock { 6'length =1 no.(गोटा)}					
	1	½ " breadth	गोटा	30	30	30	
	2	¾"	"	45	45	45	
	3	1"	"	65	65	65	
	4	1 1/2"	"	125	125	125	
	5	2"	"	140	140	140	
		PVC Conduit Pipe					
	1	1) ½ " diameter	र.मी	30	30	30	
	2	2) ¾"	"	45	45	45	
	3	3) 1"	"	65	65	65	
		Listy Pipe Accessories					
	1	½"-2" size Saddle	र.मी	8	8	8	
	2	Grips (Denmark)	गोटा	6	6	6	
	3	Steel screws	गोटा	2	2	2	
	4	PVC Tape	गोटा	15	15	15	
	8	Distribution board (DB)					
		With busbar Neutral link Earth bar and Din Rail Conforming IS13032 , IS8632, Powder coated 14SWG CRCA sheet steel housing complete.siemens;abb 'hager					
	1	4 way SPN DB Double Cover	सेट	1,050	1,050	1,050	
	2	6 way SPN DB " "	"	1,102	1,102	1,102	
	3	8 way SPN DB " "	"	1,374	1,374	1,374	
	4	12 way SPN DB " "	"	1,630	1,630	1,630	
	5	16 way SPN DB " "	"	1,742	1,742	1,742	
	6	3-4 way TPN DB Double Cover	"	2,590	2,590	2,590	
	7	6 way TPN " " "	"	2,910	2,910	2,910	
	8	8 way TPN " " " Vertical	"	5,630	5,630	5,630	
	9	12 way TPN " " " Vertical	"	7,502	7,502	7,502	
	10	50 Pair Telephone D.B.with crown tag	"	5,287	5,287	5,287	
		PVC Box for MCB					
	1	1-pole PVC box GPS	सेट	78	78	78	

सि.नं	सब सि.नं	निर्माण सामाग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT) बाहेक			कैफियत
				आ.व ०७०/०७१	आ.व ०७१/०७२	आ.व ०७२/०७३	
	2	2- pole PVC " "	"	78	78	78	
	3	3 and 4-pole PVC " "	"	126	126	126	
10	10.1	Miniature Circuits Breaker (MCB) , LEGRAND/Siemens , Abb, schnieder or equivalent					
	1	6–32 amp MCB SP (single pole)	गोटा	160	160	200	
	2	6–32 amp MCB DP (Double pole)	"	700	700	1000	
	3	6–32 amp MCB TP (Triple pole)	"	1,000	1,000	1660	
	4	32 amp MCB TPN	"	1,800	1,800	2400	
	5	40–63 amp MCB DP	"	900	900	1600	
	6	40–63 amp MCB TP	"	1,375	1,375	2560	
	7	40–63 amp MCB TPN	"	1,900	1,900	3065	
10	10.2	Miniature Circuits Breaker (MCB)KOLORS/INDO ASIAN/ GOLD MEDAL/ANCHOR WOODS/ANCHOR ROMA/VIMAL WAVE, North-west equivalent					
	1	0.5–5 amp MCB SP (single pole)	गोटा			250	
	2	6–32 amp MCB SP (single pole)	"	160	160	160	
	3	6–32 amp MCB DP (Double pole)	"	700	700	600	
	4	6–32 amp MCB TP (Triple pole)	"	1,000	1,000	1200	
	5	32 amp MCB TPN	"	1,800	1,800	1450	
	6	40–63 amp MCB DP	"	900	900	950	
	7	40–63 amp MCB TP	"	1,375	1,375	1350	
	8	40–63 amp MCB TPN	"	1,900	1,900	1800	
		Residual Current Circuit Breaker (RCCB) abb, siemens, hager, legrend, north-west lawson or equivalent					
12	1	25A to 40A ,(30mA,100,300mA) DP RCCB	गोटा	2,670	2,670	2670	
	2	63A 30mA DP RCCB	"	3,182	3,182	3182	
	3	63A 100mA DP RCCB	"	2,926	2,926	2926	
	4	63A 300mA DP RCCB	"	2,974	2,974	2974	
	5	25A to 40A ,(30mA,100,300mA) FP RCCB	"	3,278	3,278	3278	
	6	63A 30mA Four Pole RCCB	"	3,598	3,598	3598	
	7	63A 100mA Four Pole RCCB	"	3,598	3,598	3598	
	8	63A 300mA Four Pole RCCB	"	3,598	3,598	3598	
	n	Moulded Case Circuit Breaker abb, abb, siemens, hager, legrend, north-west lawson or equivalent					
		16AMP- 63AMP TP MCCB 16KA		5,594	5,594	5500	
		80AMP TP MCCB 16KA		6,147	6,147	5500	
		100AMP TP MCCB 16KA		6,147	6,147	6200	
		125AMP TP MCCB 16KA		7,875	7,875	8000	
		160AMP TP MCCB 16KA		9,675	9,675	9500	
		16AMP- 63AMP TP MCCB 25KA		6,192	6,192	6200	
		80AMP TP MCCB 25KA		6,840	6,840	6840	
		100AMP TP MCCB 25KA		6,840	6,840	6840	
		125AMP TP MCCB 25KA		11,250	11,250	11000	
		160AMP TP MCCB 25KA		13,050	13,050	13000	

सि.नं	सब सि.नं	निर्माण सामाग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT) बाहेक			कैफियत
				आ.व ०७०/०७१	आ.व ०७१/०७२	आ.व ०७२/०७३	
		200AMP TP MCCB 25KA(Adjustable)		21,150	21,150	20500	
		200AMP TP MCCB 36KA(Adjustable)		22,950	22,950	22500	
		250AMP TP MCCB 36KA(Adjustable)		27,360	27,360	26500	
		400AMP TP MCCB 50KA(Adjustable)		39,150	39,150	34500	
		630AMP TP MCCB 50KA(Adjustable)		49,950	-	47000	
		800AMP TP MCCB 50KA(Adjustable)		62,100	-	62100	
14		Manual Changeover Panel Type					
		Make ABB,Siemens,Hager DELTON or Equivalent					
		63 Amp FP	”			11280	
		80 Amp FP	”			12480	
		100 Amp FP	”			17680	
		125 Amp FP	”			18640	
		160 Amp FP	”			24480	
		200 Amp FP	”			25280	
		250 Amp FP	”			26880	
		315 Amp FP	”			34000	
15		Dome light Make Homedec, Decon, Fumagalli OR equivalent		--	--		
	i	6" Milky type decorative dome light	सेट	175	175	175	
	ii	6 " Brass base decorative dome light	”	715	715	715	
	iii	8"Milky type decorative dome light	”	220	220	220	
	iv	8 " Brass base decorative dome light	”	850	850	850	
	v	8" Silver cast Milky base Decorative Dome Light	”	1,075	1,075	1,075	
	vi	6) 8" Silver cast Black Base base Decorative Dome Light	”	550	550	550	
	vii	Decorative Ceiling luminary with round opal cover suitable for housing the one number of CFL lamp of 9W /13W/18W including CFL (Surface Mounting Dome light)	”	1,178	1,178	1,178	
	viii	Wall bracket/spout light/mirror light bulk head ordinary .Make Homedec,Decon,Fumagalli	”	225	225	225	
	ix	Wall bracket/spot light/mirror light /bulk head medium decorative.	”	350	350	350	
	x	Wall bracket/spout light/mirror light / bulk head best quality with 11/13W CFL	”	800	800	800	
	xi	1 x 11/13 watt CFL DOWN LIGHT with reflector & diffuser (conceal light) Complete Set Wipro WCG22060	”	940	940	940	
	xii	1 x 18 watt CFL Down light with reflector & diffuser (conceal light) Complete Set Wipro WCP23118	”	1,470	1,470	1,470	
	xiii	Dining lamp.	”	1,650	1,650	1,650	
	xiv	Chandlers 6-8 lamp Medium	”	14,650	14,650	14,650	
	xv	Chandlers 3-5 lamp Medium	”	10,450	10,450	10,450	
	xvi	Mirror Light Euro Light Wipro WRF21111	”	450	450	450	
	xvii	Picture light Euro Light POO2	”	650	650	650	

सि.नं	सब सि.नं	निर्माण सामग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT) बाहेक			कैफियत
				आ.व ०७०/०७१	आ.व ०७१/०७२	आ.व ०७२/०७३	
	xviii	Wall spot Light E27 60W Euro or eqv.	”	350	350	350	
	xix	Exit Light safety sign(8.24)W Make Samcon	सेट	800	800	800	
		Post top Lanterns					
	xx	Bollard Garden light small Size with CFL ,choke & clear polycarbonate dome all complete set prewired upto terminal block	”	2,500	2,500	2,500	
	xxi	Bollard Garden light medium Size with CFL ,choke & clear polycarbonate dome all complete set prewired upto terminal	”	3,000	3,000	3,000	
	xxii	Bollard Garden light Full Size with CFL ,choke & clear polycarbonate dome all complete set prewired upto terminal	”	3,375	3,375	3,375	
	xxiii	8" Globe type Post top Lamp complete set	”	1,375	1,375	1,375	
15 .	xxiv	10" Globe type Post top Lamp complete set	”	2,625	2,625	2,625	
		Roadway light luminaires Wipro, Philips , Legero or Equivalent					
	XXV I	1 x 36 W FTL street light fixture with acrylic diffuser complete set	”	2,560	2,560	2,560	
	XXV I	2 x 36 W FTL street light fixture with acrylic diffuser complete set	”	3,755	3,755	3,755	
	XXV II	300/500 watt halogen weather proof FLOOD LIGHT with glass cover Complete set	”	1,500	1,500	1,500	
	XXV III	1000 watt halogen weather proof flood light with glass cover Complete set	”	3,000	3,000	3,000	
	XXV V	150 watt HPSV weather proof flood light with glass cover lamp Complete Set	”	9,000	9,000	9,000	
	XXV i	250 watt HPSV weather proof flood light with glass cover lamp Complete Set	”	11050/-	11050/-	11050/-	
	xxvii	Single Piece deep drawn aluminum POT optics road light luminaires with clear acrylic cover 70W HPSV lamp etc. complete with all accessories,	सेट	5,100	5,100	5,100	
	xxvii i	2X18W CFL-4 Pin street light fixture with acrylic diffuser	सेट	2,205	2,205	2,205	
	xxix	1X125W HPSV street light fixture with acrylic diffuser	”	4,970	4,970	4,970	
	xxx	2X60/100W GLS aviation light fixture all complete set	”	5,520	5,520	5,520	
		CEILING FANS & EXHAUST Fans, BAJAJ/KHAITAN/ORIENT/CROMPTON/POW ERPACK C/G . Almonard or equivalent					
	a	36" size ceiling Fan	गोटा	2200.00	2200.00	2100	
16	b	42" size " "	”	2,250	2,250	2200	

सि.नं	सब सि.नं	निर्माण सामाग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT) बाहेक			कैफियत
				आ.व ०७०/०७१	आ.व ०७१/०७२	आ.व ०७२/०७३	
16	c	48" size " "	"	2,300	2,300	2250	
	d	56" size " "	"	2,500	2,500	2500	
	e	6" Exhaust Fan	"	1,450	1,450	1450	
	f	9" Exhaust Fan	"	1,750	1,750	1750	
	g	16" size wall fan	"	2,750	2,750	2750	
	h	12" size exhaust fan	"	2,500	2,500	2500	
17		BELL INDICATOR					
	a	4 way bell indicator with plate	सेट	1,219	1,219	1219	
	b	6 way " " " "	"	1,990	1,990	1990	
	c	8 way " " " "	"	2,768	2,768	2768	
	d	12 way " " " "	"	4,267	4,267	4267	
18		Materials For Earthing & Lightning Protection (sp.gr. copper =8930kg/m³)					
	a	Copper plate	के.जी	890	890	890	
	b	Copper Strip (25 x 3)mm (Appox 60"=1kg)	के.जी	1,050	1,050	1050	
	c	Copper Strip (20mm breadth x 3mm thick)	के.जी	1,050	1,050	1050	
	d	Copper Strip (12 x 3)mm	के.जी	1,050	1,050	1050	
	e	Lightning rod copper conductor Air termination set	गोटा	2,650	2,650	2650	
	f	8 SWG bare copper wire	र. मी	140	140	140	
	g	29 mm Diameter GI Pipe of 1m length	र. मी	245	245	245	
	h	30 Cm x 30 Cm Cast Iron Cover for water pouring into pit	गोटा	600	600	600	
	i	5/16 nuts & bolt with spring washer cadmium maker	गोटा	15	15	15	
	j	1/2" Diameter GI pipe for protecting the earth conductor 1.5 m in length	गोटा	190	190	190	
	k	Funnel with wire mesh	गोटा	350	350	350	
	l	Charcoal	व्याग	300	300	300	
m	Salt	के.जी	12	12	12		
19		STEEL TUBELAR POLE / WOODEN POLE					
		Steel Tubular Poles with welded plate on top and bottom (medium Gauge non Galvanized with folding System and accessories)					
	a	7 Mtr. (Bottom : 115 mm Dia 3300 mm height, 90mm Dia 2400mm height & 76 mm Dia , 1650mm height with overlapping of 200mm & 150 mm Respectively	No	11,706	11,706	11706	
	b	9 Mtr. (Bottom : 134 mm Dia. 3300 mm height, 115mm Dia 2250mm height , 90 mm Dia 2250mm height & 76mm Dia. 1650 mm height with overlapping of 200mm, 150mm, 100mm Respectively	No	12,600	12,600	12600	
	c	Steel Tubular Poles 7 Mtr. (115 mm Dia. 3100 mm height, 90mm Dia 2300mm height & 76 mm Dia and 1600mm height) with welded plate on top and bottom (medium Gauge non Galvanized with welded joints)	No	12,120	12,120	12120	
	d	7 mtr.length Wooden Pole	No	4,850	4,850	4850	
	e	9 mtr.length Wooden Pole	No	6,600	6,600	6600	
20		Modular ceiling Luminaries		--	--	--	

सि.नं	सब सि.नं	निर्माण सामाग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT) बाहेक			कैफियत
				आ.व ०७०/०७१	आ.व ०७१/०७२	आ.व ०७२/०७३	
		Fluorescent Tube light (FTL) set including Tube, condenser, starter, lamp holder, channel/batten made with pre-phosphated & powder coated CRCA steel all complete accessories pre wired upto a terminal block. PHILIPS, WIPRO, BAJAJ, HAVELLS, OSRAM, CROMPTION, MIDEA, ORIENT, PREMIER, OHMS, LEGERO or equivalent					
	a	1x20 watt FTL (Patti fittings)	सेट	450	450	450	
	b	1x40 watt FTL, Energy saving electronic striplite with electronic choke (ballast) Surface mounting (Patti Fitting)	"	752	752	752	
	c	1x20 watt FTL (Mirrolta) WRF 20120	"	850	850	850	
	d	1x40 watt FTL with attractive & functional decorative battens WRF20140	"	990	990	990	
	e	1x40 watt FTL box fittings WIF 14140	"	1,125	1,125	1125	
	f	2x40 watt FTL box fittings WIF 14240	"	1,700	1,700	1700	
	g	1x40 watt FTL Industrial channel WIF 36140	"	1,730	1,730	1730	
	h	2x40 watt FTL Industrial channel WIF 36240	"	2,220	2,220	2220	
	i	1x40 watt FTL, opalite with opal Arcylic dissuser. WCF51140	"	1,800	1,800	1800	
	j	2x40 watt FTL, oplite with opal Arcylic dissuser WCF51240	"	3,000	3,000	3000	
	k	4x20 watt FTL, oplite WCF 93418	"	5,252	5,252	5252	
	l	4x20 watt FTL mirror optic , surface/recessed mounting WCF93418	"	5,252	5,252	5252	
	m	1x40 watt FTL mirror optic with electronic choke. Surface / recessed mounting WCF 82136	"	3,450	3,450	3450	
	n	2x40 watt FTL mirror optic , surface/recessed mounting with electronic choke WVP40236	"	4,200	4,200	4200	
	o	4 x 14 watt FTL T5 with electronic ballast direct / indirect, surface / recessed with paralite P5 louver Complete set WVF20414	सेट	9,110	9,110	9110	
	p	3X14W FTL-T5 low glare fixture with specular reflector, parabolic louvers & electronic ballast surface /recessed Armstrong ceiling WVF 20314	सेट	8,005	8,005	8005	
		Compact Fluorescent Lamp (CFL) based Luminaries set all complete. PHILIPS, WIPRO BAJAJ, HAVELLS, OSRAM, CROMPTION, MIDEA, LEGERO or ISI equivalent.		--	--	--	
	q	2 x 18 W CFL recessed/surface mounting <u>mirror Optic</u> Complete Set WCP32218	"	2,600	2,600	2600	

सि.नं	सब सि.नं	निर्माण सामाग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT) बाहेक			कैफियत
				आ.व ०७०/०७१	आ.व ०७१/०७२	आ.व ०७२/०७३	
	r	1 x11 W CFL mirror Optic surface/recessed mounting complete set WVP 41111	सेट	1,780	1,780	1780	
	s	2 x11 W CFL mirror Optic Surface mounting complete set WVP41211	सेट	2,200	2,200	2200	
	t	2 x 36 watt CFL 4pin with electronic ballast direct / indirect , surface / recessed with louver Complete set WVP24236	सेट	5,890	5,890	5890	
	u	3x36 W CFL -4 pin low glare fixture with P 5 louvres & electronic ballast complete set WVP 24336	सेट	6,625	6,625	6625	
	v	Recess mounting Direct Indirect LED luninare LM15-321-XXX-60-XX				10500	
	w	Recess mounting Direct Indirect LED luninare LM11-291-XXX-57-XX				13650	
	x	Recess Surface mounted LED luminate CRCO10R038HP57				12950	
	y	High efficiency circular LED Down Lighter LD71				3150	
	z	Designer LED Streetlight with pressure die cast housing suitable for secondary roads LR01				14175	
	a	IP20 and IP 65 non integral flexible LED Strip Light LS 06/26				1050	
	b	Circular LED wall/Dome Light suitable for true ceiling LW01				3150	
	c	Square LED Wall/Dome light suitable for true ceiling LW02-101-XXX-60-XX				3150	
	d	Recess mounted indirect and direct luminaires WVP 64236				5950	
	e	2x36 Watt CFL Surface Mirror Optic WVP44236				5950	
	20.1	Down Light Fiam Make					
	1.1	FDL004 SMD7W-WWH Taiwan chip (120*90)				1260	
	1.2	FDL004 SMD7W-CW Taiwan chip				1260	
	1.3	FDL004 SMD9W-WWH Taiwan chip (145*90)				1803	
	1.4	FDL004 SMD9W-CW Taiwan chip				1803	
	1.5	FDL004 SMD15W-WWH Taiwan chip (175*90)				2745	
	1.6	FDL004 SMD15W-CW Taiwan chip				2745	
	1.7	FDL004 SMD30W-WWH Taiwan chip (200MM)				4943	
	1.8	FDL004 SMD30W-CW Taiwan chip				4943	
	1.9	FDL012 COB5W-WWH (90MM)				1264	
	2	FDL012 COB5W-CW				1264	
	2.1	FDL012 COB10W-WWH (120MM)				1922	
	2.2	FDL012 COB10W-CW				1922	
	2.3	FDL012 COB15W-WWH Taiwan chip (140MM)				4943	
	2.4	FDL012 COB15W-CW Taiwan chip				4943	
	2.5	FDL012 COB25W-WWH Taiwan chip (175MM)				6589	
	2.6	FDL012 COB25W-CW Taiwan chip				6589	
	2.7	FDL012 COB30W-WWH Taiwan chip (200MM)				8236	
	2.8	FDL012 COB30W-CW Taiwan chip				8236	
	2.9	FDL007 SMD12W-WWH Taiwan chip (130*110)				4062	
	3	FDL007 SMD12W-CW Taiwan chip				4062	
	3.1	FDL007 SMD18W-WWH Taiwan chip (165*145)				5930	
	3.2	FDL007 SMD18W-CW Taiwan chip				5930	

सि.नं		निर्माण सामाग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT) बाहेक			कैफियत
सब सि.नं	आ.व ०७०/०७१			आ.व ०७१/०७२	आ.व ०७२/०७३		
	3.3	FDLOO7 SMD24W-WWH Taiwan chip (195*175)				7412	
	3.4	FDLOO7 SMD24W-CW Taiwan chip				7412	
	3.5	FDLOO1 HP5W FBK-WWH Taiwan chip (95*110)				3074	
	3.6	FDLOO1 HP5W FBK-CW Taiwan chip				3074	
	3.7	FDLOO1 HP5W FWH-WWH Taiwan chip (80*120)				3074	
	3.8	FDLOO1 HP5W FWH-CW Taiwan chip				3074	
	3.9	FDDL005 SMD7W-WWH Taiwan chip (123MM)				1264	
	4	FDDL005 SMD7W-CW Taiwan chip				1264	
	4.1	FDLOO5 SMD12W-WWH Taiwan chip (165MM)				1646	
	4.2	FDLOO5 SMD12W-CW Taiwan chip				1646	
	4.3	FDLOO5 SMD20W-WWH Taiwan chip (200MM)				3021	
	4.4	FDLOO5 SMD20W-CW Taiwan chip				3021	
	4.5	FM3161 HP 18W-WWH Cree Led				6589	
	4.6	FM3161 HP 18W-CW Cree Led				6589	
	4.7	HD-5010-13-WWH Osram chip (86*75)				2033	
	4.8	HD-5010-13-CW Osram chip				2033	
	4.9	HD-5010-14-WWH Osram chip (115*105)				3074	
	5	HD-5010-14-CW Osram chip				3074	
	5.1	HD-5010-14-WWH Osram chip (140*125)				3844	
	5.2	HD-5010-14-CW Osram chip				3844	
	5.3	HD-5010-18-WWH Osram chip (215*200)				7631	
	5.4	HD-5010-18-CW Osram chip				7631	
	5.5	LETI 100 ROUND BLACK OPAL GX53 LED LAMP 3W				2380	
	5.6	LETI 100 SQUARE BLACK OPAL GX53 LED LAMP3W 3C1.000.000				2380	
	5.7	LUCIA WHITE OPAL				1750	
	5.8	LUCIA BLACK OPAL				1750	
	5.9	LUCIA-GD WHITE OPAL				1750	
	6	LUCIA-GD BLACK OPAL				1750	
	6.1	REMI/LUCIA WHITE OPAL				2100	
	6.2	REMI/LUCIA BLACK OPAL				2100	
	6.3	REMI/LUCIA-EL WHITE OPAL				2100	
	6.4	REMI/LUCIA-EL BLACK OPAL				2100	
	6.5	REMI/LUCIA-GD WHITE OPAL				2100	
	6.6	REMI/LUCIA-GD BLACK OPAL				2100	
	6.7	MADDI BULKHEAD WHITE OPAL				1750	
	6.8	MADDI BULKHEAD BLACK OPAL				1750	
	6.9	MADDI-VE BULKHEAD WHITE OPAL				2450	
	7	MADDI-VE BULKHEAD BLACK OPAL				1750	
	7.1	MADDI-HL BULKHEAD WHITE OPAL				1750	
	7.2	MADDI-HL BULKHEAD BLACK OPAL				1750	
	7.3	REMI/MADDI WHITE OPAL				2100	
	7.4	REMI/MADDI BLACK OPAL				2100	
	7.5	REMI/MADDI-VE WHITE OPAL				2100	
	7.6	REMI/MADDI-VE BLACK OPAL				2100	
	7.7	REMI/MADDI-HL WHITE OPAL				2100	
	7.8	REMI/MADDI-HL BLACK OPAL				2100	
	7.9	GABRI/MADDI 1L BLACK OPAL				7000	
	8	MINIGABRI/MADDI 1L BLACK OPAL				6300	
	8.1	MINIGABRI REMI/MADDI-VE 1L WHITE OPAL				6300	

सि.नं	सब सि.नं	निर्माण सामाग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT) बाहेक			कैफियत
				आ.व ०७०/०७१	आ.व ०७१/०७२	आ.व ०७२/०७३	
	8.2	GELMI WHITE OPAL E27				2800	
	8.3	GELMI BLACK OPAL E27				2800	
	8.4	GELMI-EL WHITE OPAL E27				2800	
	8.5	GELMI-EL BLACK OPAL E27				2800	
	8.6	DANZI WHITE OPAL E27				2800	
	8.7	DANZI BLACK OPAL E27				2800	
	8.8	STUCCHI WHITE OPAL E27				3150	
	8.9	STUCCHI BLACK OPAL E27				3150	
	9	CECCHI WHITE OPAL E27				3150	
	9.1	CECCHI BLACK OPAL E27				3150	
	9.2	BISSO ANNA BLACK WITH OPAL DIFFUSER				3500	
	9.3	MIKROLOT ANNA BLACK W/OPAL DIFFUSER				3500	
	9.4	IESSE LANTERN BLACK W/OPAL DIFFUSER				3150	
	9.5	MIZAR/ANNA BLACK OPAL GX53 LED LAMP 3W				7000	
	20.2	System Sensor Product (Honeywell)					
	1	Photo Electric Smoke Detector				1820	
	2	Rate of Rise Heat Detector				1820	
	3	Fixed temperature Detector				2220	
	4	Base				360	
	5	Conv. MCP, Red, with LED, 470 Ohm, with BB, India				1440	
	6	Wall mount Horn+Strobe				4000	
	7	Ceiling mount Horn+Strobe				4000	
	20.3	Exit Light Samcon make					
	1	MODEL SLM 18				12000	
	2	MODEL ELS 28				12000	
	3	MODEL ETL 210H-4LA				12000	
21		LUMINARIES Accessories (PHILIPS, HIMSTAR, BAJAJ, HAVELLS, OSRAM, GE, CROMPTION, MIDEA, ORIENT, RATHI, PREMIER, WIPRO, OHMS or ISI/CE Eqv.)					
	a	500 watt halogen rod	गोटा	225	225	225	
	b	1000 watt halogen rod	"	270	270	270	
	c	70Watt SON Lamp (Sodium Vapour)	"	810	810	810	
	d	150 watt sodium vapour bulb	"	1,260	1,260	1260	
	e	250 watt sodium vapour bulb	"	1,650	1,650	1650	
	f	20-40 watt FTL rod	"	78	78	78	
	g	20-40 watt FTL Copper chowk.	"	250	250	250	
	h	20-40W FTL Electronic Chowk with high power factor & instant flicker free start	"	400	400	400	
	i	Acryl cover for 4x20 FTL	"	960	960	960	
	j	FTL starter	"	18	18	18	
21	k	8 W to 11W, C.F.L. Direct fit	"	225	225	225	
	l	13 to 22W, C.F.L. Direct fit	"	290	290	290	
	m	15-100 watt bulb. (ISI)	गोटा	25	25	25	
	n	PL-S 9W/86 (CFL)	"	160	160	160	
	o	PL-S 11W/86 (CFL)	"	170	170	170	
	p	PL-L 36W/86 (CFL)	"	405	405	405	
	q	125W HPL-N (Mercury Vapour)	"	360	360	360	
	r	250W HPL-N	"	850	850	850	

सि.नं		निर्माण सामाग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT) बाहेक			कैफियत
सब सि.नं	आ.व ०७०/०७१			आ.व ०७१/०७२	आ.व ०७२/०७३		
		Solar LED bulb					
s		12V/2W LED bulb	"		350	350	
t		12V/3W LED bulb	"		400	400	
u		12V/4W LED bulb	"		450	450	
		COPPER CONDUCTOR /WIRE /CABLE (PER COIL=90 RM) NS marked					
	1	1/18 size p.v.c. insulated copper wire/ cable	क्वायल	1,058	1,058	920	
	2	3/22 " " "	"	1,264	1,264	1100	
	3	3/20 " " "	"	2,009	2,009	1750	
	4	7/22 " " "	"	2,862	2,862	2450	
22	5	7/20 " " "	"	4,644	4,644	4000	
	6	7/18 " " "	"	7,128	7,128	6300	
	7	7/16 " " "	"	14,742	14,742	13000	
	8	19/18 " " "	"	18,900	18,900	17500	
	9	19/16 " " "	"	39,960	39,960	35000	
	10	2\20 " " "	"			1,330	
	11	2\22 " " "	"			900	
		Multistrand Flexible wire for house wiring (90meter per coil) NS marked Eqv.					
	1	1.0 mm PVC insulated Copper wire	क्वायल	1,100	1,100	1000	
	2	1.5 mm PVC insulated Copper wire	"	1,600	1,600	1600	
	3	2.5 mm PVC insulated Copper wire	"	2,600	2,600	2350	
	4	4.0 mm PVC insulated Copper wire	"	3,950	3,950	3800	
	5	6.0 mm PVC insulated Copper wire	"	6,200	6,200	6000	
	6	10.0mm PVC insulated Copper wire	"	10,200	10,200	10000	
23		Concentric cable NS marked Eqv.	"				
	1	4mm size concentric cable	र.मी	22	22	22	
	2	6mm size " "	र.मी	25	25	25	
	3	10mm size concentric cable	र.मी	38	38	38	
	4	16mm size " "	र.मी	65	65	65	
	5	25mm size " "	र.मी	86	86	86	
	6	RG6 Coaxial cable	र.मी	22	22	22	
	7	RG59 Coaxial cable	र.मी	25	25	25	
	8	UTP cat -5 networking cable	र.मी	25	25	25	
24		Telephone Drop wire/pair cable NS marked Eqv.					
	1	² / ₂₀ Telephone drop wire	क्वायल	960	960	960	
	2	² / ₂₂ " "	क्वायल	650	650	650	
	3	2- pair cable wire (2x2x0.45) mm Heavy	र.मी	13	13	13	
	4	3- pair cable wire (3x2x0.45) mm Heavy	"	19	19	19	
	5	5- pair cable wire (5x2x0.45) mm Heavy	"	31	31	31	
	6	10- pair cable wire (10x2x0.45) mm Heavy	"	60	60	60	
	7	15- pair cable wire (15x2x0.45) mm Heavy	"	88	88	88	

सि.नं		निर्माण सामाग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT) बाहेक			कैफियत
सब सि.नं	आ.व ०७०/०७१			आ.व ०७१/०७२	आ.व ०७२/०७३		
	8	20- pair cable wire (20x2x0.45) mm Heavy	"	116	116	116	
	9	1mm drop wire	"	10	10	10	
	10	1-4 Line EPABX , with 1set programmable master telephone set of corresponding brand Panasonic, Creative, Matrix Or Egv.	सेट	7,425	7,425	7425	
	11	2-6 Line EPABX "	"	17,875	17,875	17875	
	12	3-8 Line EPABX "	"	19,940	19,940	19940	
	13	4-12 Line EPABX "	"	35,750	35,750	35750	
	14	6-16 Line EPABX "	"	48,125	48,125	48125	
	15	8-24 Line EPABX "	"	82,500	82,500	82500	
	16	8-48 Line EPABX "	"	88,275	88,275	88275	
	17	8-72 Line EPABX "	"	94,454	94,454	94454	
		Other Accessories					
	1	6" size Dome light glass	गोटा	63	63	63	
	2	8" size " " "	"	74	74	74	
	3	wall bracket glass	"	63	63	63	
	4	Fan regulator	"	263	263	263	
		Panel board double door type with locking arrangement with 2 coat of red oxide metal prime & 3 stage quality paint before final coat of enamel paint (Three phase, Neutral link, earth link) TPNE copper busbar including necessary accessories for internal wiring at the board .) (Rates of MCCB / MCB & measuring instrument are not included here .) Ankur		--	--	--	
	a	60/75/100 AMP, 9"x36"x48" size	सेट	20,790	20,790	20790	
	b	60/75/100 AMP "12x36"x48" size	"	24,750	24,750	24750	
	c	60/75/100 AMP 9"x48"x60" size	"	34,650	34,650	34650	
	d	60/75/100 AMP 12"x49"x60" size	"	41,250	41,250	41250	
	e	150/200 AMP 9"x38"x52" size	"	23,100	23,100	23100	
	f	150/200 AMP 12"x38"x52" size	"	23,100	23,100	23100	
	g	150/200 AMP 9"x42"x56 "size	"	25,724	25,724	25724	
	h	150/200 AMP 12"x42"x56" size	"	27,358	27,358	27358	
	i	250/300AMP 12"x48"x60"size	"	33,500	33,500	33500	
	j	250/300AMP 12"x52"x62" size	"	37,501	37,501	37501	
	k	400 AMP 12"x52"x66" size	"	39,920	39,920	39920	
		Panel Board measurement instrument		--	--	--	
	a	0-500 volt meter	पिस	993	993	993	
	b	60/100 Amp meter .	"	950	950	950	
	c	Panel Indicator	"	230	230	230	
	d	2 Amp glass fuse with holder 12 mm size	"	130	130	130	
	e	AMP meter selector switch	"	630	630	630	
	f	volt meter selector switch	"	690	690	690	
	g	60/100 Amp C.T. coil per set 3 Pcs	"	1,390	1,390	1,390	
	h	150-200AMP C.T coil. 3 PC / Set	गोटा	1,730	1,730	1,730	
	i	250-300 AMP " " "	"	2,350	2,350	2,350	
	j	400/500/600AMP " " "	"	3,450	3,450	3,450	
	k	Kilo watt hour energy meter single phase	पिस	2,205	2,205	2,205	

सि.नं	सब सि.नं	निर्माण सामाग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT) बाहेक			कैफियत
				आ.व ०७०/०७१	आ.व ०७१/०७२	आ.व ०७२/०७३	
	l	Kilo watt hour energy meter 3 phase direct	"	9,930	9,930	9,930	
30		Trailing Protected Industrial Plug IP44		--	--	--	
	a	16A 3P+E 400V Industrial plug	सेट	525	525	525	
	b	32 A 3p +N+E " Plug	सेट	780	780	780	
	c	32 A 3P+N+E water tight Plug IP67	सेट	1,500	1,500	1,500	
31		Access Controller with record using card and pin, Having capacity 1000 cards and 25000events,responding distance 5 cm to 15 cm, dimensin 120 x88 x18 mm built in two relay operating door	सेट	20,000	20,000	20,000	
32		Access Controller with record using card and pin, Having capacity 1000 cards and 25000events,responding distance 5 cm to 15 cm, dimension 120 x88 x18 mm built in two relay operating door (Chinese)	सेट	13,500	13,500	13,500	
33		CABLE SHOE					
	a	16 sq.mm cable shoe	गोटा	56	56	62	
	b	25 sq.mm " "	"	73	73	81	
	c	35 sq.mm " "	"	56	56	62	
	d	50 sq.mm " "	"	66	66	73	
	e	70 sq.mm " "	"	82	82	90	
	f	95 sq.mm " "	"	126	126	139	
	g	150 sq.mm " "	"	190	190	209	
	h	195 sq.mm " "	"	269	269	296	
	i	250 sq.mm " "	"	428	428	471	
34		Copper Conductor Armoured Power Cables NS marked or eqv.					
		a) 2 Core					
	1	1.5 mm ²	र.मी	106	106	100	
	2	2.5 mm ²	"	157	157	135	
	3	4.0 mm ²	"	200	200	185	
	4	6.0 mm ²	"	270	270	240	
	5	10.0 mm ²	"	405	405	360	
	6	16.0 mm ²	"	562	562	480	
	7	25.0 mm ²	"	826	826	700	
	8	35.0 mm ²	"	1,102	1,102	930	
	9	50.0 mm ²	"	1,485	1,485	1,300	
		b) 3 Core	"				
	1	1.5 mm ²	"	141	141	125	
	2	2.5 mm ²	"	184	184	175	
	3	4.0 mm ²	"	276	276	250	
	4	6.0 mm ²	"	363	363	320	
	5	10.0 mm ²	"	557	557	480	
	6	16.0 mm ²	"	762	762	670	
	7	25.0 mm ²	"	1,161	1,161	1,020	
	8	35.0 mm ²	"	1,547	1,547	1,350	

सि.नं	सब सि.नं	निर्माण सामाग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT) बाहेक			कैफियत
				आ.व ०७०/०७१	आ.व ०७१/०७२	आ.व ०७२/०७३	
34	9	50.0 mm ² Copper Conductor Armoured	"	2,111	2,111	1,850	
	10	70.0 mm ²	"	2,639	2,639	2,600	
	11	95.0 mm ²	"	4,104	4,104	3,500	
	12	120.0 mm ²	"	5,160	5,160	4,400	
	13	150.0 mm ²	"	6,332	6,332	5,400	
	14	c) 3.5 Core					
	1	25.0 mm ²	र.मी	1,568	1,568	1,220	
	2	35.0 mm ²	"	2,026	2,026	1,550	
	3	50.0 mm ²	"	2,744	2,744	2,180	
	4	70.0 mm ²	"	3,790	3,790	3,000	
	5	95.0 mm ²	"	5,227	5,227	4,000	
	6	120.0 mm ²	"	6,795	6,795	5,250	
	7	150.0 mm ²	"	8,102	8,102	6,200	
	8	185.0 mm ²	"	8,078	8,078	7,700	
	9	240.0 mm ²	"	10,519	10,519	10,100	
	10	300.0 mm ²	"	13,198	13,198	12,800	
	11	400.0 mm ²	"	17,642	17,642	16,800	
		d) 4 Core					
	1	1.5 mm ²	र.मी	165	165	150	
	2	2.5 mm ²	"	232	232	215	
	3	4.0 mm ²	"	341	341	310	
	4	6.0 mm ²	"	454	454	400	
	5	10.0 mm ²	"	681	681	600	
	6	16.0 mm ²	"	964	964	875	
	7	25.0 mm ²	"	1,476	1,476	1,300	
	8	35.0 mm ²	"	2,042	2,042	1,750	
	9	50.0 mm ²	"	2,723	2,723	2,500	
	10	70.0 mm ²	"	3,801	3,801	3,400	
34	11	95.0 mm ² Copper Conductor Armoured	"	4,539	4,539	4,600	
	12	120.0 mm ²	"	6,808	6,808	5,800	
	13	150.0 mm ²	"	8,397	8,397	7,200	
	14	185.0 mm ²	"	10,439	10,439	8,800	
	15	240.0 mm ²	"	13,503	13,503	12,000	
	16	300.0 mm ²	"	17,020	17,020	14,400	
	17	400.0 mm ²	"	22,694	22,694	19,500	
35		Copper Conductor Unarmoured Power Cables NS marked or Eqv.					
		a) 1-core					
	1	10 sq. mm.	र.मी	42	42	42	
	2	16 sq. mm.	"	63	63	63	
	3	25 sq. mm.	"	74	74	74	
	4	35 sq. mm.	"	88	88	88	
	5	50 sq. mm.	"	118	118	118	
	6	70 sq. mm.	"	153	153	153	
	7	95 sq. mm.	"	208	208	208	
	8	120 sq. mm.	"	252	252	252	
9	150 sq. mm.	"	299	299	299		
		b) 2-core					

सि.नं	सब सि.नं	निर्माण सामाग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT) बाहेक			कैफियत
				आ.व ०७०/०७१	आ.व ०७१/०७२	आ.व ०७२/०७३	
	1	1.5 sq.mm Copper Conductor Unarmoured	र.मी	65	65	70	
	2	2.5 sq.mm	"	86	86	100	
	3	4 sq.mm	"	145	145	140	
	4	6 sq.mm	"	199	199	190	
	5	10 sq.mm	"	312	312	300	
	6	16 sq.mm	"	441	441	415	
	7	25 sq.mm	"	673	673	640	
	8	35 sq.mm	"	926	926	870	
	9	50 sq.mm	"	1,246	1,246	1,200	
	10	70 sq.mm	"	1,246	1,246	1,200	
	11	95 sq.mm	"	2,428	2,428	2,250	
	12	120 sq.mm	"	2,956	2,956	2,950	
	13	150 sq.mm	"	3,642	3,642	3,700	
		c) 3-core		-	-	-	
	1	1.5 sq.mm. 3- core copper conductor	र.मी	86	86	90	
	2	2.5 sq.mm	"	129	129	130	
	3	4 sq.mm	"	194	194	190	
	4	6 sq.mm	"	280	280	270	
	5	10 sq.mm	"	441	441	425	
	6	16 sq.mm	"	646	646	620	
	7	25 sq.mm	"	990	990	950	
	8	35 sq.mm	"	1,320	1,320	1,280	
	9	50 sq.mm	"	1,816	1,816	1,800	
	10	70 sq.mm	"	2,587	2,587	2,500	
	11	95 sq.mm	"	3,642	3,642	3,400	
	12	120 sq.mm	"	4,540	4,540	4,300	
	13	150 sq.mm	र.मी	5,595	5,595	5,300	
		d) 3.5 core					
	1	25 sq.mm	र.मी	1,214	1,214	1,170	
	2	35 sq.mm Copper Conductor Unarmoured	"	1,584	1,584	1,500	
	3	50 sq.mm	"	2,164	2,164	2,100	
	4	70 sq.mm	"	2,977	2,977	2,925	
	5	95 sq.mm	"	4,117	4,117	3,950	
	6	120 sq.mm	"	5,384	5,384	5,200	
	7	150 sq.mm	"	6,440	6,440	6,150	
35		e) 4-core Copper Conductor Unarmoured					
	1	1.5 sq.mm	र.मी	108	108	110	
	2	2.5 sq.mm	"	161	161	165	
	3	4 sq.mm	"	253	253	245	
	4	6 sq.mm	"	355	355	340	
	5	10 sq.mm	"	592	592	540	
	6	16 sq.mm	"	883	883	820	
	7	25 sq.mm	"	1,320	1,320	1,280	
	8	35 sq.mm	"	1,848	1,848	1,720	
	9	50 sq.mm	"	2,481	2,481	2,400	
	10	70 sq.mm	"	3,484	3,484	3,350	
	11	95 sq.mm	"	4,751	4,751	4,550	
	12	120 sq.mm	"	6,123	6,123	5,750	

सि.नं	सब सि.नं	निर्माण सामग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT) बाहेक			कैफियत
				आ.व ०७०/०७१	आ.व ०७१/०७२	आ.व ०७२/०७३	
	13	150 sq.mm	"	7,707	7,707	7,150	
	14	185 sq.mm	"	9,607	9,607	8,800	
	15	240 Sq. mm	"	12,458	12,458	11,900	
	16	300 Sq. mm	"	15,625	15,625	14,400	
	17	400 Sq. mm	"	20,798	20,798	19,500	
36		Aluminum conductor Armoured (Power) cable NS marked or eqv.					
		a) 2-core					
	1	1.5 sq.mm	र.मी	-	-	-	
	2	2.5 sq.mm	र.मी	86	86	90	
	3	4 sq.mm	"	119	119	115	
	4	6 sq.mm	"	124	124	130	
	5	10 sq.mm	"	146	146	155	
	6	16 sq.mm	"	173	173	175	
	7	25 sq.mm	"	205	205	210	
	8	35 sq.mm	"	238	238	240	
	9	50 sq.mm	"	308	308	310	
	10	70 sq.mm	"	389	389	385	
	11	95 sq.mm	"	497	497	490	
		b) 3-core					
	1	2.5 sq.mm. Aluminum conductor Armoured	र.मी	103	103	105	
	2	4 sq.mm	"	124	124	130	
	3	6 sq.mm	"	140	140	145	
4	10 sq.mm	"	178	178	175		
5	16 sq.mm	"	200	200	200		
	6	25 sq.mm Aluminum conductor Armoured	"	259	259	270	
	7	35 sq.mm	"	319	319	325	
	8	50 sq.mm	"	410	410	415	
	9	70 sq.mm	"	529	529	525	
	10	95 sq.mm	"	675	675	480	
	11	120 sq.mm	"	821	821	810	
	12	150 sq.mm	"	999	999	975	
	13	185 sq.mm	"	1,215	1,215	1,200	
	14	240 sq.mm	"	1,490	1,490	1,470	
	15	300 sq.mm	"	1,814	1,814	1,800	
	16	400 sq.mm	"	2,349	2,349	2,250	
	c) 3.5 core						
	1	25 sq.mm.	र.मी	313	313	310	
	2	35 sq.mm	"	362	362	360	
	3	50 sq.mm	"	475	475	475	
	4	70 sq.mm	"	626	626	610	
	5	95 sq.mm	"	778	778	780	
	6	120 sq.mm Aluminum conductor Armoured	"	950	950	950	
	7	150 sq.mm	र.मी	1,123	1,123	1,140	
	8	185 sq.mm	"	1,404	1,404	1,380	
	9	240 sq.mm	"	1,739	1,739	1,720	
	10	300 sq.mm	"	2,138	2,138	2,150	
36	11	400 sq.mm	"	2,808	2,808	2,700	

सि.नं		निर्माण सामाग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT) बाहेक			कैफियत
सब सि.नं	आ.व ०७०/०७१			आ.व ०७१/०७२	आ.व ०७२/०७३		
		d) 4-core					
	1	2.5 sq.mm	र.मी	119	119	120	
	2	4 sq.mm	"	140	140	150	
	3	6 sq.mm	"	167	167	175	
	4	10 sq.mm	"	194	194	190	
	5	16 sq.mm	"	259	259	245	
	6	25 sq.mm	"	346	346	330	
	7	35 sq.mm	"	400	400	390	
	8	50 sq.mm	"	518	518	532	
	9	70 sq.mm	"	691	691	680	
	10	95 sq.mm	"	886	886	875	
	11	120 sq.mm	"	1,053	1,053	1,050	
	12	150 sq.mm	"	1,296	1,296	1,330	
	13	185 sq.mm	"	1,620	1,620	1,580	
	14	240sq.mm	"	1,998	1,998	1,980	
	15	300 sq.mm Aluminum conductor Armoured	"	2,430	2,430	2,450	
	16	400sq.mm	"	3,240	3,240	3,100	
37		Aluminium conductor unarmoured (power) cable NS marked or eqv.					
		a) 1-core					
	1	16 sq.mm	र.मी	55	55	50	
	2	25 sq.mm	"	65	65	70	
	3	35 sq.mm	"	75	75	85	
	4	50 sq.mm	"	100	100	110	
	5	70 sq.mm	"	135	135	140	
	6	95 sq.mm	"	175	175	190	
	7	120 sq.mm	"	220	220	230	
	8	150 sq.mm	"	270	270	380	
	9	185 sq.mm	"	325	325	350	
	10	240 sq.mm	"	410	410	430	
	11	300 sq.mm	"	510	510	520	
		b) 2-core Aluminium conductor unarmoured					
	1	2.5 sq.mm	र.मी	40	40	50	
	2	4 sq.mm	"	50	50	60	
	3	6 sq.mm	र.मी	60	60	75	
	4	10 sq.mm	"	80	80	95	
	5	16 sq.mm	"	90	90	100	
	6	25 sq.mm	"	125	125	140	
	7	35 sq.mm	"	160	160	180	
	8	50 sq.mm	"	210	210	230	
	9	70 sq.mm	"	285	285	290	
	10	95 sq.mm 2 core	"	360	360	390	
		c) 3-core					
	1	2.5 sq.mm	र.मी	45	45	60	
	2	4 sq.mm	"	60	60	70	
	3	6 sq.mm	"	75	75	85	
	4	10 sq.mm	"	95	95	120	

सि.नं		निर्माण सामाग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT) बाहेक			कैफियत
सब सि.नं	आ.व ०७०/०७१			आ.व ०७१/०७२	आ.व ०७२/०७३		
	5	16 sq.mm	"	125	125	140	
	6	25 sq.mm	"	185	185	200	
	7	35 sq.mm	"	225	225	250	
	8	50 sq.mm	"	310	310	330	
	9	70 sq.mm	"	410	410	440	
	10	95 sq.mm	"	530	530	580	
37	11	120 sq.mm	"	650	650	720	
	12	150 sq.mm	"	785	785	860	
	13	185 sq.mm	"	1,000	1,000	1,080	
	14	240 sq.mm	"	1,250	1,250	1,340	
	15	300 sq.mm Aluminium conductor unarmoured	"	1,550	1,550	1,700	
		d) 3.5-core					
	1	25 sq.mm	र.मी	235	235	250	
	2	35 sq.mm	"	275	275	300	
	3	50 sq.mm	"	375	375	400	
	4	70 sq.mm	"	500	500	550	
	5	95 sq.mm	"	660	660	720	
	6	120 sq.mm	"	825	825	900	
	7	150 sq.mm	"	970	970	1,080	
	8	185 sq.mm	"	1,240	1,240	1,350	
	9	240 sq.mm	"	1,550	1,550	1,700	
	10	300 sq.mm	"	1,900	1,900	2,100	
		e) 4-core core aluminium unarmoured					
	1	2.5 sq.mm	र.मी	55	55	70	
	2	4 sq.mm	"	70	70	80	
	3	6 sq.mm	"	85	85	95	
	4	10 sq.mm	"	120	120	130	
	5	16 sq.mm	र.मी	180	180	190	
	6	25 sq.mm	"	275	275	280	
	7	35 sq.mm	"	310	310	340	
	8	50 sq.mm	"	425	425	470	
	9	70 sq.mm 4	"	560	560	620	
	10	95 sq.mm	"	750	750	820	
	11	120 sq.mm	"	910	910	1,000	
	12	150 sq.mm	"	1,120	1,120	1,250	
	13	185 sq.mm	"	1,400	1,400	1,550	
	14	240 sq.mm	"	1,770	1,770	1,950	
	15	300 sq.mm	"	2,180	2,180	2,400	
38		Security Gate System					
	a	Metal Detector (ब्लाक स्क्रीपियन कम्पनी)	गोटा	16,500	16,500	16,500	
39		Air Conditioning system, Daikin, Mitsubishi heavy or Japanese eqv					
	i	0.75 TR capacity Wall Mounted split type Air Conditioning system	सेट	90,000	90,000	-	
	ii	1.0 TR capacity Wall Mounted split type Air Conditioning system	सेट	95,000	95,000	-	
		Air Conditioning system, McQuay, Panasonic, Fujiaire, Malaysian or Eqv Company					

सि.नं	सब सि.नं	निर्माण सामाग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT) बाहेक			कैफियत
				आ.व ०७०/०७१	आ.व ०७१/०७२	आ.व ०७२/०७३	
41	i	0.75 TR capacity Wall Mounted split type AirConditioning system	सेट	54,200	54,200	-	
	ii	1.0 TR capacity Wall Mounted split type Air Conditioning system	सेट	61,500	61,500	-	
		1.5 TR capacity Wall Mounted split type Air Conditioning system	सेट	76,300	76,300	-	
	iv	2.0 TR capacity Wall Mounted split type Air Conditioning system	सेट	86,400	86,400	-	
		Air Conditioning system, whirlpool or Eqv Company					
	v	0.75 TR capacity Wall Mounted split type Air	सेट	53,200	53,200	-	
	vi	1.0 TR capacity Wall Mounted split type Air	सेट	55,200	55,200	-	
	vii	1.5 TR capacity Wall Mounted split type Air	सेट	72,300	72,300	-	
	viii	2.0 TR capacity Wall Mounted split type Air	सेट	87,900	87,900	-	
42	General Lightig ANCHOR, C/G, Eqv.						
i	1 x 40 W FTL Patti fitting	सेट	245	245	245		
ii	1 x 20 W FTL Patti fitting	सेट	225	225	225		
iii	1 x 40 W FTL Box Fitting	सेट	415	415	415		
iv	1 x 20 W FTL Box fitting	सेट	405	405	405		
v	9/11W Mini mirror light with electronic Blast		345	345	345		
	suitable for PL lamp	सेट					
43	GEWISS /BEC PVC Conduit product of Italy						
	RK Range						
	1	16 mm medium rigid conduit DX 25 316	Mtr.	85	85	85	
	2	20 mm medium rigid conduit DX 25 320	"	120	120	120	
	3	25 mm medium rigid conduit DX 25 325	"	170	170	170	
	4	32 mm medium rigid conduit DX 25 332	"	245	245	245	
	5	40 mm medium rigid conduit DX 25 340	"	335	335	335	
	6	50 mm medium rigid conduit DX 25 350	"	515	515	515	
	7	63 mm medium rigid conduit DX 25 363	"	970	970	970	
	8	16 mm heavy rigid conduit DX 25 716	"	160	160	160	
	9	20 mm heavy rigid conduit DX 25 720	"	210	210	210	
	10	25 mm heavy rigid conduit DX 25 725	"	280	280	280	
	11	32 mm heavy rigid conduit DX 25 732	"	420	420	420	
	12	40 mm heavy rigid conduit DX 25 740	"	570	570	570	
	13	50 mm heavy rigid conduit DX 25 750	"	770	770	770	
	14	63 mm heavy rigid conduit DX 25 763	"	1,445	1,445	1,445	
	15	16 mm polymer cable gland GW 52 043 with fixing nut and screws	"	190	190	190	
	16	20 mm polymer cable gland GW 52 044 with fixing nut and screws	"	240	240	240	
	17	25 mm polymer cable gland GW 52 045 with fixing nut and screws	"	365	365	365	
	18	32 mm polymer cable gland GW 52 046 with fixing nut and screws	"	605	605	605	
	19	40 mm polymer cable gland GW 52 047 with fixing nut and screws	"	725	725	725	
20	50 mm polymer cable gland GW 52 048 with fixing nut and screws	"	935	935	935		
21	63 mm polymer cable gland GW 52 049 with fixing nut and screws	"	1,165	1,165	1,165		

सि.नं	सब सि.नं	निर्माण सामाग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT) बाहेक			कैफियत
				आ.व ०७०/०७१	आ.व ०७१/०७२	आ.व ०७२/०७३	
	22	16 mm shockproof polymer saddle collar clip GW 50 605	"	30	30	30	
	23	20 mm shockproof polymer saddle collar clip GW 50 606	"	35	35	35	
	24	25 mm shockproof polymer saddle collar clip GW 50 607	"	40	40	40	
	25	32 mm shockproof polymer saddle collar clip GW 50 608	"	60	60	60	
	26	40 mm shockproof polymer saddle collar clip GW 50 630	"	95	95	95	
	27	50 mm shockproof polymer saddle collar clip GW 50 631	"	115	115	115	
	28	16 mm conduit coupler DX 40 016	"	35	35	35	
	29	20 mm conduit coupler DX 40 020	"	45	45	45	
44	30	25 mm conduit coupler DX 40 025	"	55	55	55	
	31	32 mm conduit coupler DX 40 032	"	100	100	100	
	32	40 mm conduit coupler DX 40 040	"	135	135	135	
	33	50 mm conduit coupler DX 40 050	"	235	235	235	
	34	63 mm conduit coupler DX 40 063	"	445	445	445	
	35	16 mm tight bend DX 40 116	"	55	55	55	
	36	20 mm tight bend DX 40 120	"	80	80	80	
	37	25 mm tight bend DX 40 125	"	125	125	125	
	38	32 mm tight bend DX 40 132	"	230	230	230	
	39	40 mm tight bend DX 40 140	"	325	325	325	
	40	50 mm tight bend DX 40 150	"	585	585	585	
	41	63 mm tight bend DX 40 163	"	2,290	2,290	2,290	
	42	4 way junction box DX 45 004	"	650	650	650	
	43	7 way junction box DX 45 007	"	780	780	780	
	44	10 way junction box DX 45 010	"	990	990	990	
	45	Closing cap for junction box DX 47 000	"	115	115	115	
	46	16 mm inspectionable T bend DX 40216	"	115	115	115	
	47	20 mm inspectionable T bend DX 40220	"	145	145	145	
	48	25 mm inspectionable T bend DX 40225	"	190	190	190	
	49	32 mm inspectionable T bend DX 40232	"	230	230	230	
	50	16 mm inspectionable bend DX 40 316	"	95	95	95	
	51	20 mm inspectionable bend DX 40 320	"	115	115	115	
	52	25 mm inspectionable bend DX 40 325	"	150	150	150	
	53	32 mm inspectionable bend DX 40 332	"	180	180	180	
45		GEWISS/BEC Cable Tray with Cover and Accessories BRN Range					
	1	65X35 mm2 hot deep galvanised steel cable tray MV 40 100	R. Ft.	795	795	795	
	2	95X35 mm2 hot deep galvanised steel cable tray MV 40 101	"	945	945	945	
	3	125X35 mm2 hot deep galvanised steel cable tray MV 40 102	"	1,140	1,140	1,140	
	4	155X35 mm2 hot deep galvanised steel cable tray MV 40 103	"	1,280	1,280	1,280	
	5	185X35 mm2 hot deep galvanised steel cable tray MV 40 104	"	1,495	1,495	1,495	
	6	215X35 mm2 hot deep galvanised steel cable tray MV 40 105	"	1,660	1,660	1,660	
	7	245X35 mm2 hot deep galvanised steel cable tray MV 40 106	"	2,075	2,075	2,075	

सि.नं		निर्माण सामाग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT) बाहेक			कैफियत
सब सि.नं	आ.व ०७०/०७१			आ.व ०७१/०७२	आ.व ०७२/०७३		
	8	305X35 mm2 hot deep galvanised steel cable tray MV 40 108	"	2,440	2,440	2,440	
	9	365X35 mm2 hot deep galvanised steel cable tray MV 40 110	"	3,000	3,000	3,000	
	10	395X35 mm2 hot deep galvanised steel cable tray MV 40 111	"	3,185	3,185	3,185	
	11	65X50 mm2 hot deep galvanised steel cable tray MV 40 120	"	955	955	955	
	12	95X50 mm2 hot deep galvanised steel cable tray MV 40 121	"	1,145	1,145	1,145	
	13	125X50 mm2 hot deep galvanised steel cable tray MV 40 122	"	1,260	1,260	1,260	
	14	155X50 mm2 hot deep galvanised steel cable tray MV 40 123	"	1,425	1,425	1,425	
	15	185X50 mm2 hot deep galvanised steel cable tray MV 40 124	"	1,615	1,615	1,615	
	16	215X50 mm2 hot deep galvanised steel cable tray MV 40 125	"	1,805	1,805	1,805	
	17	245X50 mm2 hot deep galvanised steel cable tray MV 40 126	"	2,210	2,210	2,210	
	18	305X50 mm2 hot deep galvanised steel cable tray MV 40 128	"	2,580	2,580	2,580	
46	19	365X50 mm2 hot deep galvanised steel cable tray MV 40 130	"	3,355	3,355	3,355	
	20	395X50 mm2 hot deep galvanised steel cable tray MV 40 131	"	3,640	3,640	3,640	
	21	515X50 mm2 hot deep galvanised steel cable tray MV 40 135	"	4,450	4,450	4,450	
	22	95X65 mm2 hot deep galvanised steel cable tray MV 40 141	"	1,275	1,275	1,275	
	23	215X65 mm2 hot deep galvanised steel cable tray MV 40 145	"	2,060	2,060	2,060	
	24	305X65 mm2 hot deep galvanised steel cable tray MV 40 148	"	2,700	2,700	2,700	
	25	395X65 mm2 hot deep galvanised steel cable tray MV 40 151	"	3,740	3,740	3,740	
	26	515X65 mm2 hot deep galvanised steel cable tray MV 40 155	"	4,695	4,695	4,695	
	27	605X65 mm2 hot deep galvanised steel cable tray MV 40 157	"	5,290	5,290	5,290	
	28	125X80 mm2 hot deep galvanised steel cable tray MV 40 162	"	1,450	1,450	1,450	
	29	215X80 mm2 hot deep galvanised steel cable tray MV 40 165	"	2,205	2,205	2,205	
	30	305X80 mm2 hot deep galvanised steel cable tray MV 40 168	"	2,800	2,800	2,800	
	31	395X80 mm2 hot deep galvanised steel cable tray MV 40 171	"	4,030	4,030	4,030	
	32	515X80 mm2 hot deep galvanised steel cable tray MV 40 175	"	4,870	4,870	4,870	
		Intrusion Detection System Make Honeywell or equivalent		---	---	---	
	i	Main Controller CONTROL, FIRE/BURG COMMERCIAL VISTA-128FBP	सेट	37,720	37,720	37,720	
	ii	Smoke & Heat Detector Wireless Smoke and Head Detector	सेट	10,238	10,238	10,238	
	iii	Door Contact	सेट	2,600	2,600	2,600	

सि.नं	सब सि.नं	निर्माण सामाग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT) बाहेक			कैफियत
				आ.व ०७०/०७१	आ.व ०७१/०७२	आ.व ०७२/०७३	
47	iii	Wireless Door Contact with transmitter	सेट				
	iv	Motion Detector	सेट	4,056	4,056	4,056	
		Wireless Passive Infrared, Pet Immune Motion Detector					
	v	Panic Switch	सेट	4,778	4,778	4,778	
		Wireless Panic Transmitter					
	vi	Key	सेट	4,641	4,641	4,641	
		Wireless Key to Arm and Disarm the System					
vii	Window Contact	सेट	2,730	2,730	2,730		
	Wired door Contact with transmitter slim						
		Earth Quake Detector(JDS Inc, USA)	पिस	3,496	3,496	3,496	
		Quake Alarm					
48		Automatic Motor Operator for water motor		---	---	---	
	i	Upto 1/2 HP single phase motor	सेट	4,000	4,000	4,000	
	ii	Upto 1 HP single phase motor	सेट	5,500	5,500	5,500	
	iii	Upto 5 HP three phase motor	सेट	9,000	9,000	9,000	
49		CCTV System					
	a	Out door high speed Dome Integrated CAMERA Multi Protocal ,480 TVL,128 preset points , automatic surveillance,360 degrees horizontal rotation , AC 240V power supply , integrated heating system , highest angle speed 360 degree/ sec ,weather resistance, water resistance. robust type.		-	-	-	
	i	CANON Integrated camera chip, normal colour, 23 times optical Zoom, 10 times digital zoom	सेट	55,000	55,000	55,000	
	ii	CANON Integrated camera chip, day & night, 23 times optical Zoom, 10 times digital zoom	सेट	57,200	57,200	57,200	
	b	Indoor high speed Dome Integrated CAMERA			-	-	
	i	CANON Integrated camera chip, normal colour, 23 times optical Zoom, 10 times digital zoom	सेट	52,800	52,800	52,800	
	ii	CANON Integrated camera chip, day & night, 23 times optical Zoom, 10 times digital zoom	सेट	55,000	55,000	55,000	
50	c	VISTA Box camera with adoptor, IR view distance 25mm Mirror shutter;with mirror image switchable,white balance; auto,Horizontal resolution ; 480 TV line , system signal; NTSC/PALBlacklight compression :ON/OFF(Switchable) , AGC; ON/OFF	सेट	15,000	15,000	15,000	
	d	7" Sphirical Shilded with bracket included chip excluded Camera		8,120	8,120	8,120	
	e	i) 8 Channel DVR MJPEG Compression Type 8 Channel ionput 2 Channel output USB2.0Interface , Hard Disc > 200G, Multi-Record ,Motion Detector Function , Remote Control	सेट	33,000	33,000	33,000	
		ii) 16 Channel Alarm input , 16 Channel Record 8 channel Alarm output , Internate Explore, MPG-4 Record	सेट	49,500	49,500	49,500	

सि.नं	सब सि.नं	निर्माण सामाग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT) बाहेक			कैफियत
				आ.व ०७०/०७१	आ.व ०७१/०७२	आ.व ०७२/०७३	
	f	17" LCD Monitor SAMSUNG or Korean Eqv.	सेट	10,500	10,500	10,500	
51		Electrical Equipments					
	i	Earthing Materials (ISI or other International Standard)					
	a	6 mm thick 600mm× 600 mm G.I. Plate	No.	2,747	2,747	2,747	
	c	Funneling Mechanism with cover (mild steel)	set	600	600	600	
	d	3.2 mm thick 600mm× 600 mm Copper Plate	No.	9,240	9,240	9,240	
	e	Copper wire (10 SWG)	Mtr.	150	150	150	
	ii	Service wire (Al)					
	a.	2.5 mm ²	Mtr.	17	17	17	
	b.	4.0 mm ²	"	22	22	22	
	c.	6.0 mm ²	"	27	27	27	
	iii	Lightening Arrestor for 3 Phase .					
	a.	0.5 KV	Set	1,200	1,200	1,200	
	b.	11 KV	Set	4,200	4,200	4,200	
	c.	Cross Arms V Channel.	No	3,000	3,000	3,000	
	iv	Stay set with accessories.					
	a.	GI wire	No	1,148	1,148	1,148	
	b.	GI Plate	"	1,150	1,150	1,150	
	c.	Gay Insulator.	"	54	54	54	
	d	Elbow		100	100	100	
	e	Rod , Nut	No	432	432	432	
	f	Grip	"	48	48	48	
	v	Overhead Insulators (0.4KV)					
	a.	Sackle Insulator	No	30	30	30	
	b.	D-Iron	"	90	90	90	
	c.	Nut Bolt (3" with 8 mm Ø)	"	15	15	15	
	d.	Nut Bolt (6" with 8 mm Ø) to clamp on Poles	"	22	22	22	
	vi	Overhead Insulators with fixing accessories (11KV)					
	a.	Pin Insulator	No	180	180	180	
	b.	Disc Insulator	"	960	960	960	
	c.	Cross Arms V Channel.	"	2,640	2,640	2,640	
	vii	Sqarrel ACSR conductor 20mm²	Rm.	17	17	17	
	viii	weasel ACSR conductor 30 mm²	"	24	24	24	
	ix	Rabbit ACSR conductor 50 mm²	"	40	40	40	
	x	Dog ACSR conductor 100 mm²	"	80	80	80	
	xi	Supply of aluminium ABC cable					
		25mm square 4 core ABC cable	Rm.	150	150	150	
		50 mm square 4 core ABC cable	"	250	250	250	
		95 mm square 4 core ABC cable	"	490	490	490	
	xii	Alternator 3 Phase Brush less with compounded Excitation. (KEL)					
52	C	AMF with ATS palel for DG Ankur metal or Equivalent					
	i	5KVA AMF with ATS palel	set	22,000	22,000	22,000	
	ii	7.5KVA AMF with ATS palel	"	28,000	28,000	28,000	
	iii	10KVA AMF with ATS palel	"	35,000	35,000	35,000	

सि.नं	सब सि.नं	निर्माण सामाग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT) बाहेक			कैफियत
				आ.व ०७०/०७१	आ.व ०७१/०७२	आ.व ०७२/०७३	
	iv	15KVA AMF with ATS palel	"	45,000	45,000	45,000	
	v	20KVA AMF with ATS palel	"	65,000	65,000	65,000	
	vi	25KVA AMF with ATS palel	"	75,000	75,000	75,000	
	vii	30KVA AMF with ATS palel	"	90,000	90,000	90,000	
53	C	Solar system\Backup Power					
	a	Pure sine wave inverter					
	i	675 VA inverter	set	11,149	11,149	11,149	
	ii	875 VA inverter	"	12,234	12,234	12,234	
	iii	1500 VA inverter	"	18,434	18,434	18,434	
	iv	3 KVA inverter	"	54,317	54,317	54,317	
	b	Exide Battery					
		tubular inverter Battery					
	i	80 AH inverter Battery	set	9,646	9,646	9,646	
	ii	100 AH inverter Battery	"	11,610	11,610	11,610	
	iii	150 AH inverter Battery	"	16,212	16,212	16,212	
	iv	200 AH inverter Battery	"	20,141	20,141	20,141	
	v	75 AH tubular inverter Battery	"	12,360	12,360	12,360	
	vi	100 AH tubular inverter Battery	"	16,472	16,472	16,472	
	vii	150 AH tubular inverter Battery	"	24,240	24,240	24,240	
	viii	200 AH tubular inverter Battery	"	30,560	30,560	30,560	
	c	Solar Panel	watt	140	140	140	
54		Angel Eyes solar street light absorb energy					
		AST 1205 (12 W pv 05w led, 12.8v 5.2 Ah motion sensor)	set	28,606	28,606	28,606	
		AST 1805 (18 W pv 05w led, 12.8v 7.8 Ah motion sensor)	"	38,586	38,586	38,586	
		AST 2505 (25 W pv 05w led, 12.8v 7.8 Ah motion sensor)	"	43,798	43,798	43,798	
		AST 3612 (36 W pv 012w led, 12.8v 13 Ah motion sensor)	"	60,984	60,984	60,984	
		AE 2S18B8 (AE 2 off - grid power system, pv 18w 12.8v 7.8 Ah motion Sensor)	"	34,705	34,705	34,705	
		AE 2S25B10 (AE 2 off - grid power system, pv 25w 12.8v 10.4 Ah motion Sensor)	"	43,575	43,575	43,575	
		AE 2S36B13 (AE 2 off - grid power system, pv 36w 12.8v 13 Ah motion Sensor)	"	54,331	54,331	54,331	
55		MCB/ISOLATOR ORIENT or equivalent					
		B CURVE MCB SP 6A-32A	pole			232	
		B CURVE MCB SP 40A	pole			273	
		B CURVE MCB SP 50A-63A	pole			273	
		C CURVE MCB SP 0.5-4A	pole			273	
		C CURVE MCB SP 6-32A	pole			232	
		C CURVE MCB SP 40A	pole			433	
		C CURVE MCB SP 50-63A	pole			433	
		C CURVE MCB SPN 0.5-4A	pole			465	
		C CURVE MCB SPN 6-32A	pole			498	
		C CURVE MCB SPN 40A	pole			545	
		C CURVE MCB SPN 50-63A	pole			545	
		C CURVE MCB DP 0.5-4A	pole			599	
		C CURVE MCB DP 6-32A	pole			548	
		C CURVE MCB DP 40A	pole			599	

सि.नं		निर्माण सामाग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT) बाहेक			कैफियत
सब सि.नं	आ.व ०७०/०७१			आ.व ०७१/०७२	आ.व ०७२/०७३		
		C CURVE MCB DP 50-63A	pole			599	
		C CURVE MCB TP 0.5-4A	pole			898	
		C CURVE MCB TP 6-32A	pole			822	
		C CURVE MCB TP 40A	pole			898	
		C CURVE MCB TP 50-63A	pole			898	
		C CURVE MCB TPN 0.5-4A	pole			1171	
		C CURVE MCB TPN 6-32A	pole			1071	
		C CURVE MCB TPN 40A	pole			1171	
		C CURVE MCB TPN 50-63A	pole			1171	
		C CURVE MCB FP 0.5-4A	pole			1253	
		C CURVE MCB FP 6-32A	pole			1146	
		C CURVE MCB FP 40A	pole			1253	
		C CURVE MCB FP 50-63A	pole			1253	
		ISOLATOR DP 40A	pole			535	
		ISOLATOR DP 63A	pole			535	
		ISOLATOR DP 80-100A	pole			559	
		ISOLATOR DP 125A	pole			593	
		ISOLATOR FP 40A	pole			876	
		ISOLATOR FP 63A	pole			876	
		ISOLATOR FP 80-100A	pole			969	
		ISOLATOR FP 125A	pole			969	
		RCCB DP 25A 30mA	pole			3444	
		RCCB DP 40A 30mA	pole			3444	
		RCCB DP 63A 30mA	pole			3444	
		RCCB DP 25A 100mA	pole			3247	
		RCCB DP 40A 100mA	pole			3247	
		RCCB DP 63A 100mA	pole			3247	
		RCCB DP 25A 300mA	pole			3247	
		RCCB DP 40A 300mA	pole			3247	
		RCCB DP 63A 300mA	pole			3247	
		RCCB FP 25A 30mA	pole			4034	
		RCCB FP 40A 30mA	pole			4034	
		RCCB FP 63A 30mA	pole			4034	
		RCCB FP 25A 100mA	pole			3887	
		RCCB FP 40A 100mA	pole			3887	
		RCCB FP 63A 100mA	pole			3887	
		RCCB FP 25A 300mA	pole			3887	
		RCCB FP 40A 300mA	pole			3887	
		RCCB FP 63A 300mA	pole			3887	
56		Solar component					
	1	Solar PV Module	Per watt			126	
	2	Solar Tubular Battery (200Ah@c20,12v)	Nos			30600	
	3	Solar Tubular Battery (150 Ah@c20,12v)	Nos			23400	
	4	Solar Tubular Battery (100 Ah@c20,12v)	Nos			16200	
	5	Solar Gel Battery (100 Ah@c20,12v)	Nos			32760	
	6	Solar Gel Battery (75 Ah@c20,12v)	Nos			25020	
	7	Solar Gel Battery (40 Ah@c20,12v)	Nos			14400	
	8	Charge controller (60Ah/24V)	Nos			32400	
	9	Charge controller 45Ah/12-24-48 V	Nos			23850	
	10	Charge controller 10a/12-24 V	Nos			2700	

सि.नं	सब सि.नं	निर्माण सामाग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT) बाहेक			कैफियत
				आ.व ०७०/०७१	आ.व ०७१/०७२	आ.व ०७२/०७३	
	11	Charge controller 20a/12-24 V	Nos			4050	
	12	Solar dusk to down controller 20A/12Vwith driver curcit	Nos			4500	
	13	Solar street light 20W/10W- 12V DC with autodimming system	Nos			15300	
	14	Solar street light 40W/20W- 12V DC with autodimming system	Nos			31500	
	15	Ms pole 6 m high with rustproof enamel paint dimension 4" for buttom 3 m 3" for top 3 m	Nos			16650	
	16	Ms pole 9 m high with rustproof enamel paint dimension 4" for buttom m 6" for top 3 m	Nos			20700	
	17	40 watt solar street light	Nos			14400	
	18	20 watt solar street light	Nos			8640	
	19	12 watt solar street light	Nos			5580	
	20	Pure sine wave inverter 250 VA /12 V	Nos			7200	
	21	Pure sine wave inverter 400 VA /12 V	Nos			13500	
	22	pure sine wave inverter 1400 VA	nos			23400	
	23	Ms light Arms	Set			2250	
	24	SPV mountaining frame	set			5850	
	25	Battery box	Set			4500	
	26	Battery stand	Set			4500	

५७ बिद्युतीकरणको लागि आवश्यक पर्ने सामाग्रीहरूको स्वीकृत जिल्ला दररेट

(भ्याट बाहेक) (०७२/७३)

S.N	Particulars/Specification	Unit				
1	Pole					
1.1	Wooden pole					
1.2	8 m treated	Nos.	३३३०	3760	3760	
1.3	9 m treated	Nos.	३६१५	4200	4200	
1.4	11m concrete pole (PSC)	Nos.		8900	8900	
1.5	Bottom Section Galvanized Steel Tubular Poles	Kg		130	130	
1.6	Red Oxide Painted steel tubular Poles	Kg		105	105	
1.7	M.S. Black Pipe 15mm to 100mm	Kg		75	75	
1.8	Bottom Section Galvanized Steel Tubular Poles 11.0m with nut bolt & Washer	No.		21600	21600	
1.9	Bottom Section Galvanized Steel Tubular Poles 10.0m with nut bolt & Washer	No.		19800	19800	
###	Bottom Section Galvanized Steel Tubular Poles 9.0m with nut bolt & Washer	No.		18000	18000	
###	Bottom Section Galvanized Steel Tubular Poles 8.0m with nut bolt & Washer	No.		12600	12600	
###	Galvanized Steel 8 m Tubular (87kg)	Nos.		13050	13050	
###	Galvanized Steel 9 m Tubular (96kg)	Nos.		14400	14400	
###	Galvanized Steel 10 m Tubular (132kg)			19800	19800	
###	Galvanized Steel 11 m Tubular (168kg)	Nos.		25200	25200	

सि.नं	सब सि.नं	निर्माण सामाग्रीहरूको विवरण	एकाई	मु.अ.क. (VAT) बाहेक			कैफियत
				आ.व ०७०/०७१	आ.व ०७१/०७२	आ.व ०७२/०७३	
	2	Insulator	Nos.				
		Shackle	Nos.	५०	60	60	
		11 kvPin	Nos.	२६६	165	165	
		Disc	Nos.	७७०	494	494	
		D-iron set	Nos.	१३३	73	73	
		Distation clamp	Nos.		396	396	
	3	Earthing Set					
		Copper rod earthing (3 rods)	set	११०६२	6000	6000	
		Plate, rod, Nut bolts 600mmx600mmx 3mm	set		11062	11062	
	4	Lighting arrestor	set	१०६२	1062	1062	
		Stay set	set	८५४	915	915	
		Stay wire 7/12	kg	१२१	133	133	
	5	Conductor					
		Squirrel 1.374 ohms/km	Meter	२०	20.0	20.0	
		Weasel (0.03.sq.in) 0.9116 ohms/km	Meter	२३	24.4	24.4	
		Gofer 1.098 ohms/km	Meter	२९	29	29	
		Rabbit (0.05.sq.in) 0.5449 ohms/km	Meter	३९	41.5	41.5	
		Dog (0.1.sq.in) 0.2745 ohms/km	Meter	७८	78	78	
	6	Transformer (Neek or Equivalent Standard), Ex-Factory rate					
		15 KVA 11/0.4 kv, 3 phase	Nos	138000	#####	१९९०००	
		25KVA 11/0.4 kv, 3 phase	Nos	176400	#####	२६१४००	
		50 KVA 11/0.4 kv, 3 phase	Nos	138000	#####	३७३०००	
		100 KVA 11/0.4 kv, 3 phase	Nos	373200	#####	५९०६००	
	7	Arms					
		Top arm 300	Nos	३००	330	330	
		Cross arm 2250	Nos	२०००	2100	2100	
		Cross arm 550	Nos	२३५	250	250	
		Cross arm 1200	Nos	१२०४	1200	1200	
		Stringing of wire/Weasel (0.03.sq.in)					
	८	0.9116 ohms/km	km			8000	

नोट : माथि उल्लेखित दररेटमा नपरेका सामानहरू काठमाडौं जिल्लाले निर्धारण गरेको स्वीकृत दररेटलाई आधार मानी हुवानी दिनु पर्ने भए सो समेत जोडी नर्म्स अनुसार दर निर्धारण गरी कार्यान्वयन गर्ने निर्णय गरियो ।